



United Chemicals

TECHNICAL DATA SHEET
Ed.1 Rev: Jan 2020

ProWhite PL

Metal free polymer tanning agent

TYPICAL PROPERTIES

Appearance	: White viscous liquid
Active Substance	: 30 ± 1%
pH (10% sol.)	: 5.0 ± 0.5
Ionic Character	: Amphoteric

DESCRIPTION

ProWhite PL is developed for metal free tanning systems and recommended as a pretanning agent. It lowers down the total amount of the other tannins necessary, for instance, syntans, vegetable extracts or mineral tanning agents. **ProWhite PL** allows a high stitch and tear strength and heat resistance at the end of post-tanning processes. **ProWhite PL** gives a white crust that also yields a homogeneous and standard pastel or bright colour tones in dyeing.

APPLICATION

ProWhite PL usage is advocated after bating process for optimum penetration and normally, 4 - 8% is suitable depending upon the conditions and expectations. The addition of **POLYSOFT FWN** in fatliquoring is necessary for better tanning results and physical properties.

PACKAGING, STORAGE AND SHELF LIFE

Available in 120 kg drums or in IBC. Store in accordance with local regulations. Keep the lid closed when not in use. Store in a dry place and protect from direct sunlight. Shelf life is 12 months from the date of manufacture when stored in its original package. For more information see Safety Data Sheet.